

FLEXO

Enhanced Oil-Skimmer Technology

Floating Oils in the Degreasing Tank or Industrial Cleaning Tank COSTS YOU MONEY!

Floating "Oil-Contaminants" leave an oil-film on the parts that have been "cleaned", usually leading to additional process cost, rework and increased production break-downs.

With the FLEXO Oil-Skimmer 40.810, floating oil-residues are HISTORY!



Oil Residue Consequences are:

- ◆ Additional Cleaning Process
- ◆ Expensive Rework
- ◆ Contamination of Further Process Baths
- ◆ Poor Tank Heating Performance

Specification Model 40.810: (Standard)

Mounting:	Adjustable Swivel Magnetic Base	
Drive:	Synchronous Geared Motor	
Power:	24VAC, 5 Watt	
Unit Dimensions:	7.0" - 9.25" (Width)	(in)
	3.95" (Depth)	
	14.5" - 21.25" (Height)	
Unit Weight:	7.7 lb (3.5 kg)	
Conveying Elements:	Five (5) Nitrile O-Rings (Buna-N)	
Safety:	GFCI Power Plug w/15ft Cord	
Ambient Temperature :	- 23 → + 150 °F (-5 → 65 °C)	

Advantages:

- ◆ Superior Performance in Removing Floating Oils
- ◆ Easy and Flexible Mounting with Magnetic Base
- ◆ Quick Adjustment of Height and Tilt
- ◆ Effective Performance Regardless of Fluid Level

Options:

1. Timer
 - ◆ External Plug - In Timer Switch
2. Various Conveying Elements
 - ◆ Viton O-Rings
 - ◆ Flexible Stainless Steel Chains